

BLUEPOINT 4 ECO CURE



UV POINT SOURCE

FEATURES

- Adjustable lamp output
- High power efficiency
- High intensity


ADVANTAGES

- Long lamp life
- Short curing time
- Low production cost
- Good price/performance ratio
- Ease of use

BLUEPOINT 4 ECOCURE

bluepoint 4 ecocure is an economical high-performance point source for all applications that need maximum UV intensity. Due to its high intensity shortest cycle times can be realized.

TYPICAL UV INTENSITY DROP



The typical lamp life is approx. 3.000 hours (guaranteed lamp life 2.000 hours). It is possible to readjust the lamp output in order to maintain the intensity.



A slide out module at the front panel of the housing ensures an easy replacement of the lamp. A user-friendly operation is possible through a touch-sensitive keypad.

LAMP / SHUTTER CONTROL

The exposure time is selectable between 0.1 and 999.9 seconds. It is also possible to operate the shutter by a footswitch or a dry contact. The electrical lamp output can be adjusted in 1% steps from 60% to 100%. The unit memorizes operating hours and lamp running hours.

INTERFACES

bluepoint 4 ecocure has an interface for a software update and a dry contact for an error signal.

ADDITIONAL FEATURES

The parameter settings can be memorized on 6 storage locations and loaded when needed. The current parameter settings are maintained even after switching off the mains supply.

Error and warning messages are indicated at the display. Furthermore, bluepoint 4 ecocure has a standby function when the lamp is switched off.

Language of menu texts can be chosen between German, English, French and Italian. Three different filters are available to adapt the spectral output to the application.

LIGHT GUIDES


The following light guides are available:

- Single light guide with the diameters 3 mm, 5 mm and 8 mm
- Double, triple and quadruple light guides with a diameter of the single arms of 3 mm each
- Standard lengths of 1 m and 1.5 m
- Differing lengths on request
- Glas fiber optic
- different types of filters available, see spectrum


APPLICATIONS

bluepoint point sources are suitable for a large range of applications:

- Bonding, fixing or potting of components in the electronic, optical and medical-technical industry
- Fluorescent excitation for material testing; also suitable for automatic image processing
- High-intensity UV irradiation for chemical, biological and pharmaceutical purposes



Spectra bluepoint 4 ecocure with different filters



TECHNISCHE DATEN

max. UVA-Intensity *)	2.000 – 14.000 mW/cm ²
Typical lamp life	> 3.000 h
Timer setting range	0,1 – 999,9 sec
High pressure mercury lamp	150 W
Mains supply	90 V – 264 V 47 Hz – 63 Hz
Input current max.	2,2 A
Power rating	200 W
Dimensions (H x W x D)	155 x 450 x 310 mm
Weight	approx. 9,5 kg

*) measured with 8mm test light guide and Hoenle UV meter with UVA light guide sensor

Hoenle AG
 Nicolaus-Otto-Str. 2
 82205 Gilching
 Germany

Phone: +49 8105 2083-0
 equipment@hoenle.com

www.hoenle.com



DIN EN ISO 9001
 DIN EN ISO 14001

Operating parameters depend on production characteristics and may differ from the foregoing information. We reserve the right to modify technical data.
 © Copyright Hoenle AG. Updated 12/25